

# Manta P31

Phenyl-Functional Silane (High-Temperature Surface Modifier)

## Description

Manta P31 is a phenyl-functional trimethoxysilane that acts as a powerful surface modifier, crosslinker, and chemical intermediate. Unlike standard alkyl silanes, the phenyl group in Manta P31 provides exceptional thermal stability, making it the ideal choice for materials processed or utilized at elevated temperatures.


It effectively renders inorganic surfaces hydrophobic and improves the compatibility of fillers within organic polymer matrices. Furthermore, it is a key building block for the synthesis of phenyl-silicone resins and high-refractive-index optical materials.

It is equivalent to industry standards such as Momentive Silquest A-153, Evonik Dynasylan 9116, and Shin-Etsu KBM-103.

## Typical Physical Properties

Manta Code:	P31
Chemical Name	Phenyltrimethoxysilane
CAS NO.	2996-92-1
EINECS NO.	221-066-9
Formula	C <sub>9</sub> H <sub>14</sub> O <sub>3</sub> Si
Appearance	Colorless Transparent Liquid
Density (ρ <sub>20°C</sub> , g/cm <sup>3</sup> )	1.0620±0.0050
Refractive Index (n <sub>25/D</sub> )	1.4680±0.0050
Purity (by GC, %)	99 min

Molecular Structure



## Features

- **Exceptional Thermal Stability:** The phenyl-silicon bond is significantly more stable than alkyl-silicon bonds, providing long-term performance at temperatures exceeding 250°C-300°C.
- **Refractive Index Control:** High phenyl content allows formulators to tune the refractive index of optical resins and coatings.
- **Hydrophobicity & Dispersibility:** Efficiently treats inorganic fillers to reduce melt viscosity and improve loading levels in mineral-filled polymers.
- **Sol-Gel Versatility:** Perfectly suited for co-hydrolysis with other silanes (e.g., Manta E560, Manta

---

932) to create hybrid hard-coatings.

### Applications

#### 1. Surface Modification of Inorganic Fillers

Manta P31 is used to treat inorganic fillers such as wollastonite, aluminum trihydroxide (ATH), silica, and kaolin. It renders these fillers highly hydrophobic, ensuring better dispersibility and lower viscosity in mineral-filled polymer melts, especially for high-temperature processed engineering plastics.

#### 2. High-Temperature Resins & Specialty Siloxanes

Acts as a fundamental intermediate in the production of phenyl-silicone resins. It is used to modify the thermal properties of silicone oils and resins, enhancing their resistance to oxidation and thermal degradation in aerospace and industrial applications.

#### 3. Sol-Gel Coatings & Hard Coats

In sol-gel applications, Manta P31 is often co-hydrolyzed with alkyl silanes or epoxy silanes (like Manta E560) to produce hybrid organic-inorganic coatings. These coatings exhibit superior hardness, thermal stability, and weather resistance, commonly used for high-end decorative and protective finishes.

#### 4. Electronics & Semiconductor Packaging

Used as a critical additive in Epoxy Molding Compounds (EMC) and other electronic encapsulants. It improves the adhesion between the resin and the silica filler while maintaining the strict thermal stability required during lead-free soldering processes.

#### 5. Optical Materials

Due to the high electron density of the phenyl ring, Manta P31 is used to increase the refractive index of transparent polymers and optical coatings (e.g., LED encapsulants, lens coatings, and optical fibers).

#### 6. Hydrophobic Additive & Surface Treatment

Serves as a hydrophobic additive for other silane coupling agent systems, enhancing the water-repellency of glass, masonry, and ceramic surfaces.

### Packaging

In 25kg pail, 200kg drum and 1000kg IBC

### Safety and Storage

Keep away from heat and open flame. When stored at or below 25 °C in the original unopened containers, this product has a usable life of 24 months from the date of production.

### Contact Information

Nanjing Manta New Material Co., Ltd

Add: Room 102-247, Building 17, No. 1 Qiliqiao North Road, Nanjing Area of the China (Jiangsu) Pilot Free Trade Zone, Nanjing, China

Factory: Miaoguan Town Industrial Park, Sishui County, Jining City, Shandong Province, China

---

Mob: 0086 18962800162

Mail: [inquiry@mantasil.com](mailto:inquiry@mantasil.com)

Web: [www.mantasil.com](http://www.mantasil.com)